INFANTRY TRIPOD

Our Lightweight Infantry Tripods are a testament to innovation and resilience, engineered to meet the exacting demands of modern warfare.

KEY FEATURES

High Strength (Minimum FoS = 20).

Integrated G3 receiver with Low profile tube clamp design.

Configure feet to match Environment (snow, sand, concrete etc).

Fixed leg height and fit 40/50 Soft Mount & Yoke Pintle (all associated adaptors apply).

Corrosion resistant with 50% weight reduction (from original steel version).

Modular Design (efficient ILS, servicing, repair & redeploy).



Tripod with Soft Mount and Shoulder Bar.



Tripod with 40/50 Soft Mount.



Light-Weight Tripod with Solid Mount Yoke.



Heavy-Weight Tripod with M2 Yoke.



P10643-200 LIGHT MACHINE GUN TRIPOD

TE	CHNICAL SDECIEICATIONS
TECHNICAL SPECIFICATIONS	
Weapons Compatibility:	5.56mm GPMG, 7.62mm HMG.
Length:	stowed: 780mm; deployed: 800mm.
Width:	stowed: 150mm; deployed: 930mm.
Height:	stowed: 130mm; deployed: 410mm.
Elevation/ Depression:	+25°/-10°
Traverse:	30° (left) and 30° (right).
Mass:	~6.4ka



P10643-300 HEAVY MACHINE GUN TRIPOD

TECHNICAL SPECIFICATIONS	
Weapons Compatibility:	5.56mm, 7.62mm and 12.7mm MGs, 40mm AGL.
Length:	stowed: 1320mm; deployed: 1560mm.
Width:	stowed: 240mm; deployed:1360mm.
Height:	stowed: 140mm; deployed: 530mm.
Elevation/ Depression:	+25°/-30°
Traverse:	30° (left) and 30° (right).
Mass:	~9kg



T&E MECHANISM

KEY FEATURES

Single-hand operation.

Ergonomic traverse grip & large elevation wheel.

Compatible with 40/50 soft mount, MAG58 & MG5 with optional adaptors.

Quick release mechanism with secure pin - no loose lanyard.

Lightweight aluminium construction.

Expanded adjustment range.







Tripod Compatibility:	M3 Tripod (HMG 0.5in) & Platt Tripod - Dual Axis 3 Stage Cam Lock attachment method).
Elevation/ Depression:	+24°/-8° (initial only - varies dependent on tripod leg height).

TECHNICAL SPECIFICATIONS

Fine Elevation Range: 62mm Coarse Elevation Range: 101mm

Traverse: +/- 22° (from centre line of tripod).

Fine Traverse Range: 32mm Mass: 1.36kg Part Number: P10685

*(MEASURED ON PLATT LW INFANTRY TRIPOD WITH 40-50 SOFT MOUNT).